



The Chain Ladder® Product Specifications Version 1.00. Copyright © 2024 Fristad Plast AB www.rescuelife247.se

THE INFORMATION AND DESIGNS IN THIS DOCUMENT ARE THE EXCLUSIVE PROPERTY OF FRISTAD PLAST AB. NO PART OF THESE DESIGNS OR THE INFORMATION CONTAINED HEREIN MAY BE REPRODUCED, DISTRIBUTED, OR DISCLOSED WITHOUT THE EXPLICIT WRITTEN PERMISSION OF FRISTAD PLAST AB.

The Chain Ladder

Materials

The Chain Ladder is made of acid-resistant steel chains with footsteps made of acid-resistant steel with a UV-resistent yellow (RAL 1016) powder coating. Premium 3M reflexes are attached to each step. The low handle (optional) is made of acid-resistant stainless steel with a UV-resistent yellow (RAL 1016) powder coating. 2 pieces of 3M premium yellow reflexes are attached to each handle. The Chain Ladder is bought in meter lengths starting at 2 meters, up to 6 meter. The Weight (optional) is made of fiber-reinforced concrete, with stainless steel attachments. Attach the stainless steel attachments of The Weight with shakles at the end of The Chain Ladder.

Weight and dimensions

The Chain Ladder 2 m: 300 x 43 x 18 cm, 7,3 kg The Chain Ladder 4 m: 600 x 43 x 18 cm, 14,7 kg The Chain Ladder 6 m: 700 x 43 x 18 cm, 22,0 kg The Low Handle: 37 x 8 x 10 cm, 1,7 kg The Weight: 50 x 19 x 25 cm, 30 kg

Lifespan and Maintenance

The lifespan of The Chain Ladder depends on where it is placed and how exposed it is to the elements. To increase lifespan, we recommend reviewing The Chain Ladder every year. If necessary, it can be washed off with water and mild detergent. When The Chain Ladder is consumed, All metal parts shall be sorted as Metal waste for Recycling,

"EVERY YEAR, AT LEAST TEN PEOPLE IN SWEDEN, ARE SAVED BY A LIFEBUOY"