



The Lifebuoy Post ® Product Specifications Version 1.00.

Copyright © 2024 Fristad Plast AB www.rescuelife247.se

THE INFORMATION AND DESIGNS IN THIS DOCUMENT ARE THE EXCLUSIVE PROPERTY OF FRISTAD PLAST AB. NO PART OF THESE DESIGNS OR THE INFORMATION CONTAINED HEREIN MAY BE REPRODUCED, DISTRIBUTED, OR DISCLOSED WITHOUT THE EXPLICIT WRITTEN PERMISSION OF FRISTAD PLAST AB.

The Lifebuoy Post

Materials

The Lifebuoy Post is made of a 1,5 m aluminium tube (\emptyset 6 cm) with a UV-persistent black powder coating with a 3M yellow reflex at the top. A Lifebuoy mount (stainless steel) is attached with black composite mountings and Stainless metal bolts. The Post Base is made of Stainless steel with four holes for attaching to the ground with bolts/screws (bolts/screws are not included). **The lifebuoy is bought separately.** The Lifebuoy Post can be ordered in a custom color of choice, Powder Coating (UV-persistent).

Weight and dimensions

Pole: Ø 6 x 150 cm, 1,8 kg

Lifebuoy Holder: 52 x 57 x 17 cm, 0,9 kg Post Base: 15 x 20 x 20 cm, 1,6 kg

Total Weight: 4,3 kg

Lifespan and Maintenance

The lifespan of The Lifebuoy Post depends on where it is placed and how exposed it is to the elements. To increase lifespan, we recommend reviewing The Pole with mountings for The Lifebuoy Post every year. If necessary, it can be washed off with water and mild detergent. When The Lifebuoy Post is consumed, metal parts shall be sorted as Metal waste for Recycling, composite parts should be sorted as combustible waste for energy extraction.

"EVERY YEAR, AT LEAST TEN PEOPLE IN SWEDEN, ARE SAVED BY A LIFEBUOY"