



Rescue Ladder
Arches
[5610502]



Rescue Ladder
Distances
[5610124]

362 cm

46 cm

35 cm

7 cm

Aluminium
(Standard)



Custom Powder Coating
(Optional)

The Rescue Post Ladder

Materials

The Rescue Post Ladder is approved According to the Swedish Work Environment Authority's regulation SPCR 064, AFS 2004:3. Made of aluminium, filled with polyurethane foam (floats). 3M premium yellow reflexes. Rescue Arches and Distances made of aluminium filled with polyurethane foam (floats) are attached to the ladder with black composite mountings and Stainless steel bolts. The Rescue post Ladder can be ordered in a custom color of choice, Powder Coating (UV-persistent). The Rescue Post Ladder is available in lengths of 3.5 m or 4.5 m. The length is determined by the height of the quay. For heights above 1.8 m to the waterline, the 4.5 m ladder is required.

Weight and dimensions

Rescue Ladder 3,5 m: 362 x 46 x 7 cm (12 steps), 9 kg

Rescue Ladder 4,5 m : 462 x 46 x 7 cm (15 steps), 11 kg

Rescue Ladder Arches: 50 x 29 x Ø 4 cm, 1,4 kg

Rescue Ladder Distances: 18,5 x 8,5 x Ø3,5 cm 0,4 kg

Lifespan and Maintenance

The lifespan of the Rescue Post Ladder depends on where it is placed and how exposed it is to the elements. To increase lifespan, we recommend reviewing the Rescue Post Ladder every year, if necessary, the Ladder can be washed off with water and mild detergent. When the Rescue Post Ladder is consumed, it shall be sorted as Metal waste for Recycling.



The Rescue Post Ladder ® Product Specifications Version 1.00.

Copyright © 2024 Fristad Plast AB

www.rescuelifelife247.se

THE INFORMATION AND DESIGNS IN THIS DOCUMENT ARE THE EXCLUSIVE PROPERTY OF FRISTAD PLAST AB. NO PART OF THESE DESIGNS OR THE INFORMATION CONTAINED HEREIN MAY BE REPRODUCED, DISTRIBUTED, OR DISCLOSED WITHOUT THE EXPLICIT WRITTEN PERMISSION OF FRISTAD PLAST AB.

“EVERY YEAR, AT LEAST TEN PEOPLE IN SWEDEN, ARE SAVED BY A LIFEBUOY”