



The Rescue Post ® Product Specifications Version 1.00. Copyright © 2024 Fristad Plast AB www.rescuelife247.se

THE INFORMATION AND DESIGNS IN THIS DOCUMENT ARE THE EXCLUSIVE PROPERTY OF FRISTAD PLAST AB. NO PART OF THESE DESIGNS OR THE INFORMATION CONTAINED HEREIN MAY BE REPRODUCED, DISTRIBUTED, OR DISCLOSED WITHOUT THE EXPLICIT WRITTEN PERMISSION OF FRISTAD PLAST AB.

The Rescue Post

High-quality, maintenance-free, and type-approved products needed in a lifesaving situation, all in one place. The lifesaving post is a complete set of lifesaving equipment. In all public waterside environments, such as ports, docks, waterways, and beaches, this is the optimal way to gather all the tools for rescue.

Materials

The Rescue Ladder (1) is approved According to the Swedish Work Environment Authority's regulation SPCR 064, AFS 2004:3. Made of aluminium, filled with polyurethane foam (floats). 3M premium yellow reflexes. Rescue Arches and Distances made of aluminium filled with polyurethane foam (floats) are attached to the ladder with black composite mountings and Stainless steel bolts. The Rescue Hook (2) is made of a 5 m aluminium tube filled with polyurethane foam (floats), with a UV-resistent red powder coating, with an acid-proof stainless steel hook at the top. (1) and (2) are attached to the Rescue Pole with black composite mountings and Stainless steel bolts. The Rescue pole is made of a 3 m aluminium tube with a UV-resistent black powder coating with a 3M yellow reflex at the top. A Lifebuoy mount (stainless steel) is attached with black composite mountings and Stainless metal bolts. The lifebuoy is bought separately. The Post Base is made of Stainless steel with four holes for attaching to the ground with bolts/screws (bolts/screws are not included). The Rescue post can be ordered in a custom color of choice, Powder Coating (UV-resistent). The Rescue Ladder is available in lengths of 3.5 m or 4.5 m. The length is determined by the height of the quay. For heights above 1.8 m to the waterline, the 4.5 m ladder is required.

Weight and dimensions

Rescue Pole: Ø 6 x 300 cm, 6,5 kg Rescue Ladder 3,5 m: 362 x 46 x 7 cm (12 steps), 9 kg Rescue Ladder 4,5m : 462 x 46 x 7 cm (15 steps), 11,2 kg Rescue Ladder Arches: 50 x 29 x Ø 4 cm, 1,4 kg Rescue Ladder Distances: 18,5 x 8,5 x Ø3,5 cm, 0,4 kg Post Base: 15 x 20 x 20 cm, 1,6 kg Rescue Hook: 500 x 30 x Ø 3,5 cm, 3 kg **Total Weight: 22,9 kg** (Rescue post 3,5m)

Additional equipment (not included)

The SOLAS Approved Lifebuoy 2,5 kg (**520J201**) The Rescue Post Location Sign (**5610501**) Complete set of Pictograms for The Rescue Post (**5610234**) Amplification tube Rescue Post (**5610217**) for extreme weather conditions