



rescueline247.se


FRISTAD PLAST AB
EST. 1967

Declaration of conformity

SOLAS Rescueline 30m for Lifebuoy

Manufacturer: Fristad Plast AB
Manufacturer Address: Artavägen 2
513 32 Fristad
SWEDEN

As per product requirements in SOLAS chapter II: Personal life-saving appliances
SOLAS 2.1.4. Buoyant lifeline:

- .1 be non-kinking;
- .2 have a diameter of not less than 8mm; and
- .3 have a breaking strength of not less than 5kN.

Product description:

Braided PE/PP, no core with spliced eye, 8 braided
PE / PP Monofilament, Yellow RAL1016, UV-stability
Break load min 5,099kN

Regulations and Testing:

The product is tested in accordance with SOLAS II 2.1.4. buoyant lifeline see Test Protocol SOLAS Rescueline Lifebuoy 30m, tests are witnessed and verified by DNV Sweden, see Verification Statement DNV N142WAKAG Rev.01.

Address for technical documentation:

Expressvägen 5, 513 32 Fristad, SWEDEN

We declare that the specified equipment above complies with the requirements in SOLAS 2.1.4.

Place: Fristad

Date: 2025-03-14

Johanna Forsström, Fristad Plast AB

Fristad Plast AB
Artavägen 2
513 32 Fristad
SWEDEN

info@fristadplast.se

www.fristadplast.se

Phone +46-33-231600
Copr. ID 5561126136
VAT. No. SE556112613601